

MIXING BOX

SHW / SHX / SVW / SVX

Mixing Box For Belt Drive Units

Cabinet Fully Insulated - 3/4 inch

1" Duct Flanges Provided On Damper Openings

Dampers Can Be Positioned For Either Rear/Top Or Rear/Bottom Locations



TABLE OF CONTENTS

FEATURES	3
DIMENSIONS	3

In keeping with its policy of continuous progress and product improvement, First Co. reserves the right to make changes without notice.


MIXING BOX


SHW / SHX / SVW / SVX

FEATURES

- Cabinet fully insulated 3/4 inch.
- Attractive light gray epoxy finish on 24-60MB. Embossed galvanized cabinet on models 90-240MB.
- Crank arms and linkage rod for damper connection are furnished. Connections can be made on either side of mixing boxes. The balance of necessary linkage hardware, damper motor, and controls to be field supplied.
- Dampers can be positioned for either rear/top or rear/bottom locations.
- 1" duct flanges provided on damper openings.
- Dampers have air seals on the edges for positive closing. Models 24-90MB have single horizontal damper blades.
 Models 120-240MB have double horizontal damper blades.
- When used with water coils units, a "freezestat" must be installed to prevent coil damage caused by low ambient conditions.

DIMENSIONS





MIXING BOX – DIMENSIONS										
Model	Α	В	С	D	E	F	Damper Size (NOM)	Shipping Weight (lbs.)		
24MB	16"	16-3/8"	18-1/8"	8"	6"	1-1/16"	2-16 x 8"	40		
36MB	16"	16-3/8"	27-5/8"	8"	6"	1-1/16"	2-26 x 8"	58		
48MB	18"	20-3/8"	29-1/8"	10"	8"	1-1/16"	2-27 x 10"	65		
60MB	18"	20-3/8"	36-1/8"	10"	8"	1-1/16"	2-34 x 10"	78		
90MB	18"	25-3/8"	45-1/8"	10"	8"	1-11/16"	2-42 x 10"	110		
120MB	20"	30-3/8"	48-1/8"	12"	10"	1-1/16"	2-46 x 12"	135		
180MB	22"	37-7/8"	57-1/8"	14"	12"	1-9/16"	2-54 x 14"	190		
240MB	22"	50-1/2"	57-1/8"	14"	24"	1-9/16"	2-54 x 14"	210		

Cat. No. CMB1203 (Replaces CMB1193)



AMERICAN-MADE. FAMILY OWNED.



FIRST CO.
P.O. BOX 270969 - DALLAS, TEXAS 75227
PH. (214) 388-5751 | FAX (214) 388-2255
WWW.FIRSTCO.COM

SEPTEMBER 2025